

DIGITAL MEDIA APPLICATION INSTRUCTIONS

ColorPrint Easy

For Use On: 100% cotton | Poly/cotton blends | 100% polyester | Leather



Print and Cut Instructions:

- Print, cut, and weed material
- No dry time required!
- Mask with TTD Easy mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- · Apply design at 300°F / 149°C
- Use medium pressure for 15 seconds
- · Peel carrier warm

Laundering:

- · Wait 24 hours before first wash
- · Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent and Solvent Inks - Not for use with Inkjet or Laser printers

ColorPrint Extra PU

Print and Cut Instructions:

- Print, cut, and weed your design
- No dry time required!
- Mask with TTD Easy mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 305°F / 150°C
- Use medium pressure for 15 seconds
- · Peel carrier hot or warm

- · Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- · Wash inside-out for best results

Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers

ColorPrint PU (Matte/Gloss) For Use On: 100% cotton | Poly/cotton blends | 100% polyester | Leather | Lycra®/Spandex

Print and Cut Instructions:

- Set heater/dryer to 113°F/45°C
- If heavy saturation ink, dry 1 hour before cutting
- Print, cut, and weed material
- Mask with TTD Easy mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 295°F / 146°C
- Use medium pressure for 15-20 seconds · Peel carrier hot
- Laundering:
- Wait 24 hours before first wash
- · Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers

DigiBrick™

CPSIA

Print and Cut Instructions:

- Print, cut and weed your design
- · Mask with TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 311°F / 155°C
- Use medium/firm pressure for 25 seconds • Peel carrier cold
- Laundering:
- · Wait 24 hours before first wash
- Machine wash cold with mild detergent Do not bleach or dry clean
- Dry on low dryer setting

Compatible with Eco-Solvent and Solvent Inks - Not compatible with Inkjet or Laser printers

EasvPSV™ Printable

For Use On: Glass | Wood | Plastic | Metal | Ceramic

Print and Cut Instructions:

- Print and cut your design (do not reverse/mirror)
- · Weed excess vinyl
- Remove application tape's paper liner and place on top of EasyPSV
- Burnish with a Squeegee
- * Place on desired object and burnish with a squeegee
- peel away the application tape

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 311°F / 155°C
- Use medium/firm pressure for 5 seconds
- Peel carrier Hot
- Re-cover design and press for 20 seconds

Laundering:

- · Wait 24 hours before first wash
- · Machine wash cold with mild detergent Do not bleach or dry clean
- Dry on low dryer setting

Hi-5 Print Matte

For Use On: 100% cotton | Poly/cotton blends | 100% polyester

Print and Cut Instructions:

- Print, cut, and weed your design
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

Compatible with Eco-Solvent, Solvent, Latex, and Mimaki UV Inks - Not compatible with Inkjet or Laser printers

- Preheat garment for 2-3 seconds
- Apply design at 250°F / 120°C
- Use medium pressure for 5 seconds
- · Peel carrier hot

Laundering:

- · Wait 24 hours before first wash
- · Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers

SparklePrint™



1-2022

Print and Cut Instructions:

- Print, cut, and weed material
- No dry time required!
- Mask with TTD Easy mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 311°F / 155°C
- Use medium/firm pressure for 15 seconds Peel carrier hot

Laundering:

- · Wait 24 hours before first wash
- · Machine wash cold with mild detergent
- Dry on low dryer setting
- Do not bleach or dry clean
- · Wash inside-out for best results

Compatible with Eco-Solvent, Solvent, and Latex Inks - Not compatible with Inkjet or Laser printers

























DIGITAL MEDIA APPLICATION INSTRUCTIONS

S-PrintTM (Matte)



Print and Cut Instructions:

- Print, cut, and weed your design
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Cover design with Heat Transfer Cover Sheet
- Apply design at 248°F / 120°C
- Use medium pressure for 10-15 seconds
- Peel carrier hot

Laundering:

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Sublithin® Soft

Compatible with Eco-Solvent and Solvent Inks - Not compatible with Inkjet or Laser printers



1-2022

Print and Cut Instructions:

- Print, cut, and weed your design
- Mask with TTD Easy Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 265°F / 130°C
- Use medium pressure for 15 seconds
- Peel carrier warm

Laundering:

- Wait 24 hours before first wash
- · Machine wash cold with mild detergent
- Do not bleach or dry clean
- · Hang item to dry

Compatible with Eco-Solvent, Solvent and Latex Inks - Not compatible with Inkjet or Laser printers











